




P.T.B.-PRIMER

Solvent free



Application

Ready-to-use, colourless primer for walls, floors, and ceilings. P.T.B.-PRIMER lowers porosity and reinforces the substrate. Suitable surfaces are: plaster work on cement base, plaster work on gypsum base, gypsum plaster board, gypsum plaster blocks, concrete, ...
P.T.B.-PRIMER is suitable for indoor as well as outdoor use.



Directions for use

P.T.B.-PRIMER should always be applied to a porous, clean, healthy, dust and oil-free substrate. Shake well before use.
P.T.B.-PRIMER should be generously and undilutedly applied with a brush or a roller. Strongly absorbing undergrounds (such as aerated concrete, plasterwork on gypsum base, and the like) should be treated twice.
Drying time: about 2 to 3 hours.



Special applications

P.T.B.-PRIMER can also be used to enhance the characteristics of mortar in terms of adhesion, elasticity, water impermeability, mould-protection, and the like. For such purpose, it is necessary to replace the water used in the preparation by either undiluted P.T.B.-PRIMER or in a ratio of 1 part by volume P.T.B.-PRIMER for 1 part by volume water.
P.T.B.-PRIMER can be used as basic layer - on the adhesive side - to protect certain types of natural stone (for instance, white marble) against spot blemishes and staining. To be applied in 1 or 2 layers. It is recommended that a test be carried out first.




Remarks

The application tools should be cleaned with water directly after use. Do not use at temperatures below + 5°C or on top of a substrate where the temperature is below + 5°C.
Store in a dry and frost-free place.



Refer to clause p. 2.



Mixing ratio	Consumption	Packaging
Undiluted	± 0,050 to 0,150 l/m ² , depending on the porosity of the substrate	1l and 5 l
Colours	Drying time	Application temperature
becomes colourless after application	± 2 to 3 hours	+ 5 till + 30 °C