


Super elastic tile glue  
(Solvent free)



**Qualities**



P.T.B.-PASTAFLEX is a ready-for-use super elastic tile glue allowing to glue faience, ceramics, glass mosaics, etc. in a simple manner to a flat and clean surface. Appropriate surfaces are: concrete, masonry, plaster, cementation works, cellular concrete, chipboards, veneer boards, etc. Floors provided with floor heating can also be tiled with P.T.B.-PASTAFLEX.

Applications in very fine layers are possible. With P.T.B.-PASTAFLEX one never has leftovers nor waste, and moistening of the tiles on the surfaces is no longer required.

P.T.B.-PASTAFLEX is a waterproof tile glue that can be used both inside and outside.

P.T.B.-PASTAFLEX can be used for applications in “wet rooms “ such as e.g. showers, bathrooms, kitchens, etc.

P.T.B.-PASTAFLEX cannot be used in a permanently wet environment (e.g. swimming pools). In such applications, we can recommend our products P.T.B.-KLEEFCEMENT and FLEXcement®.

Due to its super elasticity, P.T.B.-PASTAFLEX bridges deformations of the surface and/or the glued material that are present in practice.

After curing, P.T.B.-PASTAFLEX does not present any deterioration and is insensitive to frost.

Mixing ratio	Consumption	Packaging
Undiluted	± 0,8 to 1,5 kg/m <sup>2</sup>	1 kg (18 pcs/cardboard box), 7 kg and 14 kg
Colours	Open time	Application temperature
broken white	± 15 min	+ 10 till + 30 °C

## Directions for use

P.T.B.-PASTAFLEX is always applied on a clean, dust and oil-free surface. Boards serving as a surface must always be fixed in a stable way before the installation of the tiles is started. The adhesive is applied in a thin layer using an adhesive trowel or trowel, and then without delaying, the product is distributed evenly with an adhesive trowel. Next, the dry tiles are pressed on to the surface with a slightly twisting action. The tiles must be installed within fifteen minutes after application of the glue. Stopping of the joints of the tiles with pointing mortar is done after the glue has dried. Refer to our products P.T.B.-VOEGSPECIE (Standard and water-repellent), P.T.B.-JOINT BREED and P.T.B.-EPOXY JOINT.

Curing time: approx. 7 days

Conservation, processing and drying of the glue must be done away from frost.

After use, the tools are cleaned with water without delaying so that the adhesive cannot remain stuck to the tools.

In case the tiles shift down a little because of their weight, the appropriate spacers will be used.

## Special application

P.T.B.-PASTAFLEX can also be used to glue tiles onto tiles (only for indoor use). For the curing of the glue, the surface must be able to absorb moisture. The existing tiles must be scoured off. Next, one applies a fine layer of P.T.B.-PASTAFLEX, which will be left curing. Now, one can install the new tiles. Refer also to FLEXcement®.

Refer to clause p. 2.

